

SPECIFICATIONS

MAX TEMPERATURE
 Standard Seals: 121°C/250°F
 High Temp Seals: 207°C/405°F
 Geo Seals: 207°C /405°F + Steam

IMPERIAL

OD (in)	ID (in)	Length (ft)	Weight (lb)	Pump Open Area (in ²)	Stroke Up (in)	Stroke Down (in)	Max Rotating DLS (°/100ft)	Max Sliding DLS (°/100ft)	Overpull to Yield (lbs)	Torsional Yield (lbf-ft)
5.00	2.25	24.0	1,000	11.0	12.0	12.0	17	20	400,000	21,000
6.50	2.50	19.8	1,600	16.8	8.0	8.0	12	18	560,000	45,000
6.75	2.50	21.0	1,600	16.8	8.0	8.0	12	18	560,000	45,000
8.00	3.00	22.5	3,000	30.7	12.0	12.0	10	15	500,000	77,000
9.62	3.00	23.0	4,200	38.7	12.0	12.0	6	14	1,400,000	125,000

METRIC

OD (mm)	ID (mm)	Length (m)	Weight (kgs)	Pump Open Area (cm ²)	Stroke Up (cm)	Stroke Down (cm)	Max Rotating DLS (°/30m)	Max Sliding DLS (°/30m)	Overpull to Yield (daN)	Torsional Yield (N-m)
127	57	7.3	454	71.2	30.5	30.5	17	20	177,929	28,472
165	64	6.0	726	108.4	20.3	20.3	12	18	249,100	61,012
171	64	6.4	726	108.4	20.3	20.3	12	18	249,100	61,012
203	76	6.9	1,361	198.1	30.5	30.5	10	15	222,411	104,398
244	76	7.0	1,905	249.7	30.5	30.5	6	14	622,751	169,478